amaverick X3 max x ds turbo r

HIGHLIGHTS

DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with front and rear four-way adjustable seats
- 154 hp turbocharged and intercooled Rotax® ACE engine

POWERFUL

• TTX suspension with

PRECISE

- industry leading travel Ultra efficient and •
- Advanced airflow dynamics
- lightweight chassis Shiftless QRS-X transmission Sharpest handling features



- SPECIFIC TO X ds PACKAGE
- 14-in. aluminum beadlock wheels with 29-in. Maxxis Bighorn[†] 2.0 tires
- Front and rear 20-in. suspension travel
- Fully adjustable FOX[†] 2.5 PODIUM RC2[†] Piggyback shocks •
- Painted color options •

ENGINE	TURBO R
Туре	154 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC $^{\text{\tiny M}}$) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

Triple Black / TURBO R Circuit Yellow / TURBO R

TIRES / WHEE	LS
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) aluminum beadlock

	DIMENSIONS /	CAPACITIES
	LxWxH	164.4 x 64 x 65 in. (417.7 x 162.5 x 165.1 cm)
pression and	Wheelbase	135 in. (342.9 cm)
	Ground Clearance	13 in. (33 cm)
ay bar	Estimated Dry Weight	1,735 lb (786.9 kg)
mpression,	Cage / Chassis	Dual-phase 980 steel, fully welded
rol	Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
piston calipers piston calipers	Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Center console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
	Fuel Capacity	10.5 gal (40 L)

			Fuel Capacity	10.5 gal (40 L)
FEATURES				
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour	Protection	0	bumper, full High Molecular Weight skid plate and quarter-doors
	meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter ty	be DC outlet in central console
		Lighting		adlights and tail lights with ie Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Enco	ded Security System (D.E.S.S.™) with Start/ Stop button
WARRANTY				
Factory		6-months limited wa	arranty	

Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, teatures, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-byos vide vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.





Can-AmOffroad.com

- ٠

Power Steering	Tri-Mode Dynamic Power Steering (DPS™)	
SUSPENSIONS		
Front Suspension	Double A-arm with sway bar 20 in. (50.8 cm) travel	
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments	
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 20 in. (50.8 cm) travel	
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control	

DIARLS	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers