MAVERICK X3 MAX X rs TURBO R

DEFIANT

- Trademark Can-Am DNA with 154 hp turbocharged and next generation design
- Low seating position
- Ergo-Lok cockpit with front

POWERFUL

- intercooled Rotax® ACE engine
- Advanced airflow dynamics
- and rear four-way adjustable Shiftless QRS-X transmission •

PRECISE

- · TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features

Triple Black / TURBO R Gold & Can-Am Red / TURBO R

SPECIFIC TO X rs PACKAGE

- 72 in. (182.9 cm) wide
- 14-in. aluminum beadlock wheels with 30-in. Maxxis Bighorn[†] 2.0 tires
- 22-in. of suspension travel
- Fully adjustable FOX[†] 3.0 PODIUM RC2[†] remote reservoir shocks with bypass
- Full roof and heavy-duty HMW skid plate
- Painted color options

ENGINE	TURBO R
Туре	154 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R/ P
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS	
Front Suspension	Trophy truck inspired Double A-arm with sway bar 22 in. (55.9 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 22 in. (55.9 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments


BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	Maxxis Bighorn 2.0 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Wheels	14-in. (35.6 cm) aluminum beadlock

DIMENSIONS / CAPACITIES		
LxWxH	165.5 x 72 x 66 in. (420.3 x 182.9 x 167.6 cm)	
Wheelbase	135 in. (342,9 cm)	
Ground Clearance	14 in. (35.6 cm)	
Estimated Dry Weight	1,840 lb (834.6 kg)	
Cage / Chassis	Dual-phase 980 steel, fully welded	
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Center console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)	
Fuel Capacity	10.5 gal (40 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat	Protection	Integrated front bumper, heavy-duty full High Molecular Weight (HMW) skid plate, quarter-doors and full roof
	belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage





Can-AmOffroad.com

